



2007 CA ACCESSIBILITY
REQUIREMENTS

Total Number of Parking Spaces in Lot or Garage	Minimum required number of Spaces
1-25	1
26-50	2
51-75	3
76-100	4
101-150	5
151-200	6
201-300	7
301-400	8
401-500	9
501-1,000	*
1,001 & over	**

TABLE NO. 11B-6 SPACES REQUIRED

The following table Establishes the number of accessible parking space required:

*Two percent of total.

**Twenty plus one for each 100, or fraction thereof over 1,001.

1129 B.5 Identification of Parking Spaces for Off-Street Parking Facilities. Each parking space reserved for persons with physical disabilities shall be identified by a reflectorized sign permanently posted immediately adjacent to and visible from each stall or space, consisting of a profile view of a wheelchair with occupant in white on dark blue background. The sign shall not be smaller than 70 square inches in area and, when in a path of travel, shall be posted at a minimum height of 80 inches from the bottom of the sign to the parking space finished grade. Signs may also be centered on the wall at the interior end of the parking space at a minimum height of 36 inches from the parking space finished grade, ground or sidewalk. Spaces complying with Section 3107A (b) 2 shall have an additional sign stating "Van-Accessible" mounted below the symbol of accessibility.

An additional sign shall also be posted in a conspicuous place at each entrance to off-street parking facilities, or immediately adjacent to and visible from each stall or space. The sign shall not be less than 17 inches by 22 inches in size with lettering not less than 1 inch in height, which clearly and conspicuously states the following:

"Unauthorized vehicles parked in designated accessible spaces not displaying distinguishing placards or license plates issued for persons with disabilities may be towed away at owner's expense. Towed vehicles may be reclaimed at _____

or by telephoning _____"
Blank spaces are to be filled in with appropriate information as a permanent part of the sign.

In addition to the above requirements, the surface of each accessible parking space or stall shall have a surface identification duplicating either of the following schemes:

1. By outlining or painting the stall or space in blue and outlining on the ground in the stall or space in white or suitable contrasting color a profile view depicting a wheelchair with occupant; or